



















SL-HT cable ties black
for external use and/or at high temperatures
inside serrations
PA 6.6 black H.T.



SES-QUICK
-40 to +110°C



• **SL-HT cable ties**
resistant to UV radiation

type	artide number	dimensions length x width mm	maximum bundle Ø mm	tensile strength mini. (daN)	 pcs		
85/24	SL HT-M	0186 0110 010	85 x 2,4	16	8	1000	
85/24	SL HT-C	0186 0111 010	85 x 2,4	16	8	100	
100/25	SL HT-M	0186 0120 010 *	100 x 2,5	20	8	1000	
100/25	SL HT-C	0186 0121 010	100 x 2,5	20	8	100	
150/26	SL HT-M	0186 0122 010	150 x 2,6	40	8	1000	
150/26	SL HT-C	0186 0123 010	150 x 2,6	40	8	100	
200/26	SL HT-M	0186 0180 010 *	200 x 2,6	50	8	1000	
200/26	SL HT-C	0186 0181 010	200 x 2,6	50	8	100	
145/34	SL HT-M	0186 0130 010 *	145 x 3,4	35	13	1000	
145/34	SL HT-C	0186 0131 010	145 x 3,4	35	13	100	
210/34	SL HT-M	0186 0142 010	210 x 3,4	55	13	1000	
210/34	SL HT-C	0186 0143 010	210 x 3,4	55	13	100	
300/36	SL HT-M	0186 0232 010	295 x 3,6	76	13	1000	
300/36	SL HT-C	0186 0233 010	295 x 3,6	76	13	100	
370/36	SL HT-C	0186 0242 010	370 x 3,6	102	13	100	
160/46	SL HT-M	0186 0124 010	160 x 4,6	38	22	1000	
160/46	SL HT-C	0186 0125 010	160 x 4,6	38	22	100	
185/46	SL HT-M	0186 0140 010	185 x 4,6	47	22	1000	
185/46	SL HT-C	0186 0141 010	185 x 4,6	47	22	100	
250/46	SL HT-M	0186 0126 010	250 x 4,6	60	22	1000	
250/46	SL HT-C	0186 0127 010	250 x 4,6	60	22	100	
300/46	SL HT-M	0186 0146 010	300 x 4,6	83	22	1000	
300/46	SL HT-C	0186 0147 010	300 x 4,6	83	22	100	
380/47	SL HT-C	0186 0150 010	380 x 4,7	109	22	100	
180/76	SL HT-C	0186 0132 010	180 x 7,6	36	54	100	
240/76	SL HT-C	0186 0144 010	240 x 7,6	50	54	100	
300/76	SL HT-C	0186 0148 010	300 x 7,7	76	54	100	
365/76	SL HT-C	0186 0160 010	365 x 7,6	100	53	100	
550/90	SL HT-C	0186 0163 010	550 x 8,9	155	79	100	
780/90	SL HT-C	0186 0162 010	775 x 8,9	230	79	100	



* Packed per 10 bundles of 100 pieces.

 Bag available with a European suspension hole.